SUPPLY AND EXHAUST METAL DOOR GRILLES

MVMP Series

IIII	 of concentration of	-	1111	1111		1111	
			-	-	-	-	-

Application

- Mounting in door leaves of bathrooms, kitchens, etc.
- Suitable for installation into window sills for correct warm air distribution from radiators.
- Used to arrange correct air circulation in premises.

Design

- Made of polymer-coated or galvanized steel and are suitable for painting in various colours.
- Quality materials and zinc-phosphate treatment ensure coating integrity and provide reliable corrosion protection.
- Screw fixing.
- Modifications with an insect screen are available.
- Various decorative ornaments.
- Minimum door leaf thickness for grilles with fixing lugs is 30 mm.


Grille modifications

- MVMP... basic steel models with white polymer coating and screw fixing.
- **MVMP...s** steel grilles with white polymer coating equipped with a protecting insect screen.
- MVMP...Zn galvanized steel grilles with screw fixing.
- MVMP...s Zn galvanized steel grilles with screw fixing and a protecting insect screen.
- MVMP...«colour code» colourful polymer painted models.

Colour modifications



Decorative ornament types



MVMP...-2





MVMP...-5

MVMP...-6

Overall dimensions

Model		Dime	nsions, [[mm]	Number of	Air page [m2]	
IVIOUEI	L	Н		h	А	sections	Air pass, [m ²]
MVMP 250x80	250	80	236	66	0,8	5	0,0055
MVMP 350x80	350	80	338	68	0,8	6	0,0067
MVMP 430x80	430	80	418	68	0,8	7	0,0083
MVMP 450x80	450	80	438	68	0,8	8	0,0094
MVMP 475*80	475	80	461	71	0,8	10	0,0110

